

Note: When a Waterco Multicyclone Centrifugal Water Filter is installed within a swimming pool filtration system it is strongly recommended that no granular pool chemicals are added to the pool water through the pool skimmer box, unless there is the option to bypass the Multicyclone.

				$\sim \Lambda$		ADA
		- (U).	- TAN	Con A	UNI.	-10/-

Waterco (USA) Inc Augusta, Georgia, USA Tel: +1 706 793 7291

Waterco Canada Longueuil, Quebec, Canada Tel: +1 450 748 1421 Waterco (Europe) Limited Sittingbourne, Kent, UK Tel: +44 (0) 1795 521 733 Waterco (NZ) Limited Auckland, New Zealand

Tel: +64 9 525 7570 Waterco (C) Limited Guangzhou, China Tel: +86 20 3222 2180

NSW - Sydney (Head Office) Tel: +61 2 9898 8600 Waterco (Far East) Sdn Bhd Selangor, Malaysia Tel: +60 3 6145 6000

PT Waterco Indonesia Jakarta, Indonesia Tel: +62 21 4585 1481

Waterco Singapore Intl Pte Ltd Nehsons Building, Singapore Tel: +65 6344 2378



DISTRIBUTED BY:









## 1st STAGE CENTRIFUGAL WATER FILTRATION

- Pulls out debris up to 30 microns
- Ideal for new and existing installations
- Dramatically reduces waste water
- Extends filter cycles
- Requires NO additional pad space
- Simple installation
- Works with all equipment brands
- 2 year warranty



WWW.WATERCO.US

### **Ease filter workload**

MultiCyclone pre-filters up to 80% of the filter's incoming dirt load easing the workload of the swimming pool filter. As the MultiCyclone intercepts more and more dirt, the flow rate remains unchanged.

- Improving pool water circulation
- Enhancing the performance of the automatic pool cleaner and in floor cleaning system
- Allowing effective pool vacuuming without burdening the pool filter
- Minimising filter maintenance and saving water



### **Minimise backwash frequency**

The installation of a MultiCyclone as a pre-filter to a sand filter can reduce its backwash frequency to once per year, resulting in a saving of up to 7,000 litres of water per year for an average domestic sized swimming pool.

# Minimise cartridge cleaning and replacement

The installation of a MultiCyclone as a pre-filter to a cartridge filter can reduce filter cartridge cleaning and replacement to once per swimming season and even up to once per year, depending on the size of the cartridge filter.



#### **Centrifugal water filtration**

The MultiCyclone works on the basis of centrifugal water filtration. There are no moving parts to wear and tear, and no filter media to clean or replace.



### Simple maintenance

The MultiCyclone is easily cleaned by opening its purge valve. Only 15 litres of water is discharged to cleanse the MultiCyclone. 40mm /  $1^{1}/_{2}$ " quick fit unions

UV and corrosion proof

Hydraulically efficient design

12 multiple hydro cyclones

Glass filled reinforced thermoplastic

Clear poly carbonate sediment chamber

25mm / 1" sediment purge valve

- i. Incoming water enters 12 hydro cyclones tangentially, generating a strong centrifugal effect.
- ii. The sediment is spun out to the hydro cyclone's wall, and then spirals down to the sediment chamber\*.
- iii. The filtered water migrates towards the centre of the hydro cyclone where the flow reverses and spirals upwards through the outlet.
- iv. Accumulation of sediment can be visibly monitored through the MultiCyclone's clear sediment chamber.

\*Note:

The MultiCyclone is designed to filter sediment that is heavier than water, floating debris cannot be filtered out by centrifugal filtration.

### **Specifications**

Model	Connection Ports	Minimum Flow	Maximum Flow	Maximum Pressure
MultiCyclone12	40mm / 1 <sup>1</sup> /2"	40lpm / 2.4m³/hr	300lpm / 18m³/hr	350 kPa(50psi)